

Fact sheet YouV-Lite[®] GSF

June 2020

Printing | Characteristics

- Flexo and rollercoater printing process
- Curing by UV radiation
- Sheetfed and webfed printing
- Film- and paperbased substrates
- Low odor

Technical details

Appearance:	High Gloss
Reactivity:	High
Overprintable:	Yes (test required according to specific conditions)
Hotfoilstampable:	Yes (test required according to specific conditions)
CoF:	Medium
Flexibility:	Medium
Viscosity (DIN 4 23°C):	37-46 sec

Preparation | Handling | Processing

- Wear protective gloves, clothing and eye protection
- Stirr sufficiently
- Clean press well before and after printing
- Cleaning of YouV-Lite[®] products with acetate or alcohol
- Choose application volume according to substrate, speed and other conditions
- Choose speed according to UV equipment
- Check curing & blocking

Packaging | Order volume

Available packaging sizes:	A25 = 25kg canisters (standard) B26 = 200kg drums (on request) IBC = 1'000kg containers (on request)
Minimum order volume:	A25 = 1 palette / 600kg (per palette 24x25kg) B26 = 4 palette / 3200kg (per palette 4x200kg) IBC = 3 palette / 3000kg (per palette à 1x1000kg)
Place order at:	www.youv-lite.com